

Eliante Aqua IP65 COB Spotlight – Recessed, 7W to 40W

Product code: JS-ELT-HR



Types and sizes

TYPE	WATTAGE	SIZE	CUT-OUT
Ø75 mm cut-out	7W	Ø85 × H70 mm	Ø75 mm
Ø75 mm cut-out	10W	Ø85 × H70 mm	Ø75 mm
Ø75 mm cut-out	12W	Ø85 × H70 mm	Ø75 mm
Ø95 mm cut-out	12W	Ø110 × H78 mm	Ø95 mm
Ø95 mm cut-out	15W	Ø110 × H78 mm	Ø95 mm
Ø95 mm cut-out	18W	Ø110 × H78 mm	Ø95 mm
Ø125 mm cut-out	18W	Ø135 × H91 mm	Ø125 mm
Ø125 mm cut-out	25W	Ø135 × H91 mm	Ø125 mm
Ø125 mm cut-out	30W	Ø135 × H91 mm	Ø125 mm
Ø155 mm cut-out	30W	Ø180 × H106 mm	Ø155 mm
Ø155 mm cut-out	40W	Ø180 × H106 mm	Ø155 mm

Specifications

Light source	Bridgelux / Cree	Body colours	Black, White
Driver	Philips / Fulham / Osram	Material	Aluminium Die Casting
Efficiency	120-140 lm/W	IP rating	IP65
Colour temperatures	2700K, 3000K, 3500K, 4000K, 5000K, 5600K, 6500K	Features	Lens: Herculux, Tri-colour with RF, Bluetooth and WiFi dimming available
Beam angles	24° , 45° , 55°	Accessories	Honeycomb Mesh
Ring colours	White, Matt Black, Shining Black, Chrome		

LED options

Ultra (5yr) · Performance (3yr) · Standard (2yr) · Essential (2yr) · 3-in-1 Colour Switch (2yr) · Dali Dimmable DT-6 (5yr) · Dali Tunable DT-8 (5yr) · RF+BLE Tunable (3yr) · RF+BLE Tunable Eco (2yr) · Zigbee Tunable Eco (2yr) · Zigbee Dimming (3yr) · Triac Dimmable (2yr) · Triac Tunable Eco (2yr) · 1-10V Dimmable (2yr) · RF Dimming (2yr) · RF+BLE Dimming (3yr) · RF Tunable Eco (2yr) · RF Tunable Essential (2yr) · RGB + Tunable White (3yr)

Not every option is offered on every size.

