Aluminium In-Ground LED Uplighter

IP67 · 220VAC / 12VDC / 24VDC · Aluminium body

Lighting	
Wattage / lumens	3W · 220 lm; 9W · 860 lm; 12W · 1050 lm; 18W · 1450 lm; 24W · 1900 lm; 36W · 2800 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	4° / 8° / 15° / 24° / 36° / 60°
LED	SMD
Honeycomb	Optional
CRI	>85

Electrical	
Input voltage	220VAC / 12VDC-24VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 3C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 67
Impact rating (IK)	08
Body	Made of Die-cast Aluminium with SS Ring
Pre-mount casing	ABS material
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 67 / IP 68 Connectors on request




Product view


Versions available on our website

Size & Wattage	3W – 50mm · 9W – 90mm · 12W – 125mm · 18W – 150mm · 24W – 150mm · 36W – 210mm
LED Colour	Single Colour(27k/3k/4k/6k) · RGB · RGBW
Input Voltage	220VAC · 12V DC · 24V DC


Dimensions (mm)




3W




9W




12W



18W



24W



36W

CE · **IP67** · **Class I earthing**

Honeycomb Louvre Available on Request · Stainless Steel-316 Marine Grade Ring on Request · Brass Finish Ring on Request