Linear Underwater LED Light

IP68 · 12VDC / 24VDC · PC tube / stainless steel linear body

Lighting	
Wattage / lumens	10W · 400 lm; 18W; 20W · 1600 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K
Beam angle	Diffused / 15° / 24° / 36° / 15°×30°
LED	SMD
CRI	>85

Electrical	
Input voltage	12VDC-24VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 2C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 68
Impact rating (IK)	08
Body	Round tube: PC body; linear fittings: Stainless Steel Profile
Glass	Clear toughened glass
Accessories	IP 68 Connectors on request



Product view




Alternative view


Versions available on our website

Size & Wattage	Surface-mount round tube diffused 10W · Surface linear with lens 18W · Surface linear clear 20W · Surface linear diffused 20W
LED Colour	Single Colour(27k/3k/4k/6k)
Input Voltage	12V DC · 24V DC


Dimensions (mm)



Round tube



Surface fitting



Recessed fitting

Family dimension references; round tube, surface and recessed housings differ.

CE · **IP68** · **Class I earthing**

Extra Cable Length Available on Request · Round tube: PC body; linear fittings: SS body. · Lumen values are stated only where specified for that wattage.

