Stainless Steel Underwater Fountain Surface Spot Light

IP68 · 12VDC / 24 VDC · SS304 body

Lighting	
Wattage / lumens	2W; 3W · 180 lm; 6W · 360 lm; 9W · 540 lm; 12W · 720 lm; 18W · 1080 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	15° / 24° / 36° / 60° / Asymmetrical / Diffused
LED	SMD
CRI	>85

Electrical	
Input voltage	12VDC-24 VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 2C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 68
Impact rating (IK)	08
Body	Made of SS 304 Grade Steel
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 68 Connectors on request



Product view




Alternative view


Versions available on our website

Size & Wattage	2w(1ledx2w)-50mm · 3w(3ledx1w)-90mm · 6w(3ledx2w)-90mm · 9w(3ledx3w)-90mm · 12w(6ledx2w)-125mm · 18w(9ledx2w)-150mm
LED Colour	Warm White (2.7k) · Warm White (3k) · Neutral White (4k) · White (6k) · Red · Green · Blue · Amber · RGB · RGBW
Input Voltage & IP rating	12VDC · 12V · 24VDC


Dimensions (mm)




Ø50 mm



3W / 6W / 9W



12W



18W

CE **IP68** **Class I earthing**

Extra Cable Length Available on Request · Stainless Steel-316 Marine Grade on Request · SS Tripod Stand on Request · Lumen values are stated only where specified for that wattage.



