Stainless Steel In-Ground LED Uplighter

IP67 · 220VAC / 12VDC / 24VDC · SS304 body

Lighting	
Wattage / lumens	1W · 72 lm; 3W; 6W · 480 lm; 9W · 720 lm; 12W · 960 lm; 18W · 1440 lm; 24W; 36W
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	4° / 8° / 15° / 24° / 36° / 60°
LED	SMD
Honeycomb	Optional
CRI	>85

Electrical	
Input voltage	220VAC / 12VDC-24VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 3C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 67
Impact rating (IK)	08
Body	Whole fixture made of SS-304 grade steel
Pre-mount casing	ABS material
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 67 / IP 68 Connectors on request



Product view




Alternative view


Versions available on our website

Size & Wattage	1w(1ledx1w)-42mm · 1w(1ledx1w)-50mm · 3w(1ledx3w)-70mm · 3w(1ledx3w)-50mm · 3w(3ledx1w)-70mm · 3w(3ledx1w)-90mm · 6w(3ledx2w)-90mm · 9w(3ledx3w)-90mm · 12w(6ledx2w)-125mm · 18w(9ledx2w)-150mm · 24w(12ledx2w)-150mm · 36w(18ledx2w)-180mm
LED Colour	Single Colour(27k/3k/4k/6k) · Coloured(Red/Green/Blue/Amber) · RGB · RGBW
Input Voltage & IP rating	220vac(IP-67) · 12vdc/24vdc(IP-68)


Dimensions (mm)




Ø40 mm




Ø50 mm




Ø70 mm




Ø90 × 120 mm




Ø90 × 125 mm



Ø125 mm



Ø150 mm · housing 1



Ø150 mm · housing 2

Housing drawings are family references. Confirm the dimensions and protection rating of the selected version before installation.

CE **IP67** **Class I earthing**

Drive Over Application on request · Honeycomb Louvre Available on Request · Stainless Steel-316 Marine Grade on Request · Lumen values are stated only where specified for that wattage.