Stainless Steel Recessed Underwater Pool Light

IP68 · 12VDC / 24VDC · SS304 body

Lighting	
Wattage / lumens	3W · 180 lm; 6W · 360 lm; 9W · 540 lm; 12W · 720 lm; 18W · 1080 lm; 24W · 1440 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	15° / 24° / 36° / 60° / Asymmetrical
LED	SMD
CRI	>85

Electrical	
Input voltage	12VDC-24VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 2C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 68
Impact rating (IK)	08
Body	Made of SS 304 Grade Steel
Pre-mount casing	ABS material
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 68 Connectors on request



Product view




Alternative view


Versions available on our website

Size & Wattage	3w(3ledx1w)-90mm · 6w(3ledx2w)-90mm · 9w(3ledx3w)-90mm · 12w(6ledx2w)-125mm · 18w(9ledx2w)-150mm · 24w(12ledx2w)-150mm
LED Colour	Warm White (2.7k) · Warm White (3k) · Neutral White (4k) · White (6k) · Red · Green · Blue · Amber · RGB · RGBW
Input Voltage & IP rating	12vdc · 24vdc


Dimensions (mm)




Ø50 mm




3W




6W




9W



12W



18W



24W

CE **IP68** **Class I earthing**

Extra Cable Length Available on Request · Stainless Steel-316 Marine Grade on Request