Stainless Steel Surface Mounted Underwater Pool Light

IP68 · 12VDC / 24VDC · SS304 body

Lighting	
Wattage / lumens	3W · 180 lm; 6W · 360 lm; 9W · 540 lm; 12W · 720 lm; 18W · 1080 lm; 20W
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	15° / 24° / 36° / 60° / Asymmetrical
LED	SMD
CRI	>85

Electrical	
Input voltage	12VDC-24VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 2C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 68
Impact rating (IK)	08
Body	Made from SS 304 Grade Steel
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 68 Connectors



Product view




Alternative view


Versions available on our website

Size & Wattage	3w(1ledx3w)-75mm · 6w(3ledx2w)-75mm · 9w(3ledx3w)-125mm · 12w(6ledx2w)-125mm · 18w(9ledx2w)-125mm · 20w-20mm
LED Colour	Warm White (2.7k) · Warm White (3k) · Neutral White (4k) · White (6k) · Red · Green · Blue · Amber · RGB · RGBW
Input Voltage & IP rating	12vdc · 24vdc


Dimensions (mm)




3W




6W




9W



12W



18W



Diffused · Ø230 mm

The diffused housing drawing is a family reference. Confirm the diameter of the selected version before installation.

CE **IP68** **Class I earthing**

Stainless Steel-316 Marine Grade on Request · Lumen values are stated only where specified for that wattage.