Tiltable In-Ground Directional LED Uplighter

IP67 · 220VAC / 12VDC / 24VDC · Aluminium body


Lighting	
Wattage / lumens	9W · 720 lm; 18W · 1400 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	4° / 15° / 24° / 36°
LED	SMD
Honeycomb	Optional
CRI	>85

Electrical	
Input voltage	220VAC / 12VDC-24VDC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 3C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 67
Impact rating (IK)	08
Body	Body made of Die-cast Aluminium with SS-304 Ring
Pre-mount casing	ABS material
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 67 / IP 68 Connectors



Product view




Alternative view


Versions available on our website

Size & Wattage	9w(3ledx3w)-125mm · 18w(9ledx2w)-180mm
LED Colour	Warm White (2.7k) · Warm White (3k) · Neutral White (4k) · White (6k) · Red · Green · Blue · Amber · RGB · RGBW
Input Voltage & IP rating	220vac(IP-67) · 12vdc/24vdc(IP-67)


Dimensions (mm)




Ø120 mm · single LED



Ø120 mm · three LEDs



Ø120 mm · directional



Ø210 mm

Family dimension references. Confirm the selected housing size before installation.

CE **IP67** **Class I earthing**

Honeycomb Louvre Available on Request · Stainless Steel-316 Marine Grade Ring on Request



