Tree-Mounted Outdoor Spotlight

IP65 · 220Vac / 24Vdc · Aluminium body

Lighting	
Wattage / lumens	Please ask our team for the wattage
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam angle	15° / 24° / 36° / 60°
LED	SMD / COB
CRI	>85

Electrical	
Input voltage	220Vac / 24Vdc
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 3C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 65
Impact rating (IK)	07
Body	Made of Die cast Aluminium with powder coated
Glass	Clear toughened glass of 4mm thickness
Accessories	IP 67 Connectors



Product view




Tree strap installation


Versions available on our website

LED Colour Single Colour


Dimensions (mm)




Housing · Ø30 mm




Housing · Ø50 mm




Housing · 155 mm




Housing · Ø65 mm · type 1



Housing · Ø65 mm · type 2



Hood · 63 × 55 mm



Hood · 120 × 75 mm

Housing sizes of the spike-light family.

CE **IP65** **Class I earthing**

Snoot & Honeycomb Louvre Available on Request · Tree strap included in the website product.

