Outdoor Wall Mount Up Down Light

IP65 · 220VAC · Aluminium body

Lighting	
Wattage / lumens	6W · 480 lm; 12W · 960 lm; 18W · 1440 lm; 24W; 36W · 2880 lm; 50W · 4100 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K / RGB
Beam angle	10° / 15° / 24° / 36° / 60°
LED	SMD / COB
CRI	>85

Electrical	
Input voltage	220VAC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 3C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 65
Impact rating (IK)	07
Body	Made of Die cast Aluminium with powder coated
Glass	Clear toughened glass of 4mm thickness
Accessories	IP 67 Connectors



Product view




Alternative view


Versions available on our website

Shape	Round · Square
Size & Wattage	6W · 12W · 18W · 24W · 36W · 50W
LED Colour	Single Colour(27k/3k/4k/6k) · RGB


Dimensions (mm)




Round · Ø60 mm




Round · Ø100 mm



Round · Ø140 mm



Round · Ø200 mm



Square · 65 mm

CE · **IP65** · **Class I earthing**

Honeycomb Louvre & Snoot Available · Snoot Option Available on Request · Lumen values are stated only where specified for that wattage.