Outdoor Wall Mount Up Light

IP65 · 220VAC · Aluminium body

Lighting	
Wattage / lumens	3W · 240 lm; 6W · 480 lm; 12W · 960 lm; 18W · 1440 lm; 24W; 40W · 3200 lm
Colour temperature (CCT)	2700K / 3000K / 4000K / 6000K
Beam angle	3° / 15° / 24° / 36° / 60°
LED	SMD
CRI	>85

Electrical	
Input voltage	220VAC
Life span	50000 Hours
Power factor	>0.9
Power cable	High Temperature Silicon 3C×1mm²
Dimming	Triac / PWM / 1-10V / DALI

Build & protection	
Ingress protection	IP 65
Impact rating (IK)	07
Body	Made of Die cast Aluminium with powder coated
Glass	Clear toughened glass of 5mm thickness
Accessories	IP 67 Connectors; Honeycomb Louvre & Snoot Option Available



Product view




Alternative view


Versions available on our website

Shape	Round · Square
Size & Wattage	3W · 6W · 12W · 18W · 24W · 40W
LED Colour	Single Colour(27k/3k/4k/6k)


Dimensions (mm)




Round · Ø60 mm




Round · Ø60 mm



Round · Ø100 mm



Round · Ø140 mm



Square · 65 mm

CE **IP65** **Class I earthing**

Snoot & Honeycomb Louvre Available on Request · Lumen values are stated only where specified for that wattage.