



OCT-XMAXX

OCT-XMAXX Is An Innovative Led Base Well Glass Luminaire Maxx Has The Potential To Save Up To 0% Of Energy Without Compromising Lighting Parameters In The Existing Installation. Axel Is Widely Used In Various Applications In Diversified Sector. It Is Developed By Using Advance Technology And Requisition Tool In Compliance With Quality Standards. Available In Both Opal & Clear Vandal Resistant Polycarbonate Diffuser.

APPLICATION

- Highmasts
- Container berths, docks, ports
- Airport aprons, flyovers & bridges
- Railway marshalling yards
- Security lighting, sport lighting
- Shopping malls, building facade



OCT-XMAXX

HI BAY LIGHT

Model No.	OCT-XMAXX-50XM
INPUT VOLTAGE	110-280V
INPUT CURRENT	215mA
WATT	50W
OPERATING FREQUENCY	50 Hz
POWER FACTOR	≥0.95
OUTPUT VOLTAGE	30-40 V
OUTPUT CURRENT	1.2 A
DRIVER EFFICIENCY	≥90%
LED DRIVER	Constant current LED Driver
SENSOR PRINCIPAL	HFPD Int. Detector+ DOP
SENSING TIME	0.012 msec
OPERATING FREQUENCY	4.8GHz+ DO Effect
DIM/ON-OFF	AUTO ON/OFF
TRANSMISSION POWER	<0.2mW
DETECTION RANGE	Upto 9 Mtrs
DETECTION ANGLE	120° to 360°
HOLD TIME	40 Sec
BUILT IN SURGE PROTECTION	4 KV
LED LUMEN EFFICIENCY	±130lm/W
CCT (AS PER ANSI)	6500K/4000K/3000K
SIZE (D*H)mm	140X115
BIS	Approved
INGRESS PROTECTION	IP65



ENERGY SAVING



MOTION DETECTION



AUTO ON/OFF



UPTO 9M
DETECTION RANGE



ECO- FRIENDLY



OVER VOLTAGE
PROTECTION



NO UV RADIATION



IP65 WATERPROOF



WORKING

Turn On Light At Full Bright
When Person/object Detect In
Range And Turn Off Automatically
When They Move Out.



OCT-XMAXX

HI BAY LIGHT

Model No.	OCT-XMAXX-50DM
INPUT VOLTAGE	110-280V
INPUT CURRENT	215mA
WATT	50W
OPERATING FREQUENCY	50 Hz
POWER FACTOR	≥0.95
OUTPUT VOLTAGE	30-40 V
OUTPUT CURRENT	1.2 A
DRIVER EFFICIENCY	≥90%
LED DRIVER	Constant current LED Driver
SENSOR PRINCIPAL	HFPD Int. Detector+ DOP
SENSING TIME	0.012 msec
OPERATING FREQUENCY	4.8GHz+ DO Effect
DIM/ON-OFF	AUTO DIM (50W to 10W)
TRANSMISSION POWER	<0.2mW
DETECTION RANGE	Upto 9 Mtrs
DETECTION ANGLE	120° to 360°
HOLD TIME	35 Sec
BUILT IN SURGE PROTECTION	4 KV
LED LUMEN EFFICIENCY	±130lm/W
CCT (AS PER ANSI)	6500K/4000K/3000K
SIZE (D*H)mm	140X115
BIS	Approved
INGRESS PROTECTION	IP65



ENERGY SAVING



MOTION DETECTION



AUTO DIMMABLE



UPTO 9M
DETECTION RANGE



ECO- FRIENDLY



OVER VOLTAGE
PROTECTION



NO UV RADIATION



IP65 WATERPROOF



WORKING

TURN On light at Full Bright
when Person/Object detect in
Range and TURN Dim to 25%
when they move out.