



OCT-XPHANTOM Unique Lighting Design Creating a Different Scenario With OCT-iSense Technology. High Efficiency And Full Opal Diffuser Generates Comfortable Environment And Excellent Energy Saving.

Available Wattage - 40W

Available In-3000K/4000K/6500K



# OCT-XPANTOM

| MODEL No                  | OCT-XPHT-40DM               |
|---------------------------|-----------------------------|
| Input Voltage             | 110-300V                    |
| Input current             | 175 mA                      |
| Watt                      | 40W                         |
| Operating frequency       | 50 Hz                       |
| Power factor              | ≥0.95                       |
| Output voltage            | 80V                         |
| Output current            | 450-500 mA                  |
| Driver efficiency         | ≥90%                        |
| Operating temperature     | (-15°C TO 55°C)             |
| Led driver                | Constant current LED Driver |
| Built in surge protection | 4 KV                        |
| Internal wiring           | Insulated Cu wire           |
| Led                       | LM80 certified LED          |
| Led life                  | 50000 hours                 |
| Led lumen efficiency      | ≥3800 lm                    |
| Cct (as per ansi)         | 6500K/4000K/3000K           |
| CRI                       | ≥80                         |
| Sensor principal          | HFPD Int. Detector+ DOP     |
| Sensing time              | 0.012 msec                  |
| Operating frequency       | 4.8GHz+ DO Effect           |
| Dim/on-off                | Dim (40W to 8W)             |
| Transmission power        | <0.2mW                      |
| Detection range           | Upto 9 Mtrs                 |
| Detection angle           | 120° to 360°                |
| Hold time                 | 35 Sec                      |
| Main housing              | Aluminium                   |
| PC diffuser               | PC diffuser                 |
| Hardwares                 | SS & MS Zinc plated         |
| Ingress protection        | IP20                        |
| Housing type              | linear light                |
| SIZE (L*W*H)mm            | 1200X28X36                  |
| BIS                       | Approved                    |
| EMC                       | Approved                    |



Energy Saving



Motion Detection



Auto Dimmable



Upto 9m  
Detection Range



Eco-Friendly



Thermal protection



No Uv Radiation



Heavy Duty Batten



## WORKING

TURN On light at Full Bright when Person/Object detect in Range and TURN Dim to 25% when they move out.



# OCT-XPHANTOM

| MODEL No                  | OCT-XPHT-40XM               |
|---------------------------|-----------------------------|
| Input Voltage             | 110-300V                    |
| Input current             | 175 mA                      |
| Watt                      | 40W                         |
| Operating frequency       | 50 Hz                       |
| Power factor              | ≥0.95                       |
| Output voltage            | 80V                         |
| Output current            | 450-500 mA                  |
| Driver efficiency         | ≥90%                        |
| Operating temperature     | (-15°C TO 55°C)             |
| Led driver                | Constant current LED Driver |
| Built in surge protection | 4 KV                        |
| Internal wiring           | Insulated Cu wire           |
| Led                       | LM80 certified LED          |
| Led life                  | 50000 hours                 |
| Led lumen efficiency      | ≥3800 lm                    |
| Cct (as per ansi)         | 6500K/4000K/3000K           |
| CRI                       | ≥80                         |
| Sensor principal          | HFPD Int. Detector+ DOP     |
| Sensing time              | 0.012 msec                  |
| Operating frequency       | 4.8GHz+ DO Effect           |
| Dim/on-off                | Auto on/off (40W to 8W)     |
| Transmission power        | <0.2mW                      |
| Detection range           | Upto 9 Mtrs                 |
| Detection angle           | 120° to 360°                |
| Hold time                 | 35 Sec                      |
| Main housing              | Aluminium                   |
| PC diffuser               | PC diffuser                 |
| Hardware                  | SS & MS Zinc plated         |
| Ingress protection        | IP20                        |
| Housing type              | linear light                |
| SIZE (L*W*H)mm            | 50X70X1200                  |
| BIS                       | Approved                    |
| EMC                       | Approved                    |



Energy Saving



Motion Detection



AUTO ON/OFF



Upto 9m  
Detection Range



Eco-Friendly



Thermal protection



No Uv Radiation



Heavy Duty Batten



## WORKING

Turn On Light At Full Bright  
When Person/object Detect In  
Range And Turn Off Automatically  
When They Move Out.