



OCT-XPRO

MODEL No	OCT-XPRO-15DM
Input Voltage	110-300V
Input current	65 mA
Watt	15W
Operating frequency	50 Hz
Power factor	0.95
Output voltage	80V
Output current	180-190 mA
Driver efficiency	≥90%
Operating temperature	(-15°C TO 55°C)
Led driver	Constant current LED Driver
Built in surge protection	4 KV
Internal wiring	Insulated Cu wire
Led	LM80 certified LED
Led life	50000 hours
Led lumen Efficiency	≥1650lm
CCT	6500K/4000K/3000K
CRI	≥80
Sensor principal	HFPD Int. Detector+ DOP
Sensing Time	0.012 msec
Operating Frequency	4.8GHz+ DO Effect
Dim/on-off	Dim (15wto5w)
Transmission power	<0.2mW
Detection range	Upto 9 Mtrs
Detection angle	120° to 360°
Hold time	20 Sec
Main housing	Poly Carbonate
PC diffuser	PC diffuser
Hardwares	SS & MS Zinc plated
Ingress protection	IP20
Housing Type	A80
SIZE (L*W*H)mm	115X115X35
BIS	Approved
EMC	Approved



Motion Sensor



Auto Dimmable (15 To5w)



Time 20 Seconds



High Voltage Protection



Eco Friendly



High Brightness



Save Energy



WORKING

Turn On Light At Full Bright
When Person/Object Detect In
Range And Turn Dim To 5w After 20 Second
When They Move Out.