



OCT-XTUBO

10W

MOTION SENSOR
ENABLED CONCEALED LIGHT

AUTO **ON**
OFF



OCT-XTUBO

MODEL No	OCT-XTUBO -10XM
Input Voltage	110-300V
Input current	45 mA
Watt	10W
Operating frequency	50 Hz
Power factor	0.95
Output voltage	80V
Output current	95-100 mA
Driver efficiency	≥90%
Operating temperature	(-15°C TO 55°C)
Led driver	Constant current LED Driver
Built in surge protection	4 KV
Internal wiring	Insulated Cu wire
Led	LM80 certified LED
Led life	50000 hours
Led lumen Efficiency	≥900 lm
CCT	6500K/4000K/3000K
CRI	≥80
Sensor principal	HFPD Int. Detector+ DOP
Sensing Time	0.012 msec
Operating Frequency	4.8GHz+ DO Effect
Dim/on-off	ON/OFF
Transmission power	<0.2mW
Detection range	Upto 9 Mtrs
Detection angle	120° to 360°
Hold time	40 Sec
Main housing	Poly Carbonate
PC diffuser	PC diffuser
Hardwares	SS & MS Zinc plated
Ingress protection	IP20
Housing Type	Concealed
SIZE (L*W*H)mm	115X115X35
DXH	110X 40
EMC	Approved



Motion Sensor



Motion On/off



Time 40 Seconds



High Voltage Protection



Eco Friendly



High Brightness



Save Energy



WORKING

TURN On light at Full Bright when Person/Object detect in Range and TURN Off Automatically when they move out.